






Electrically isolated base plate  
Industrial standard package  
Simplified mechanical design, rapid assembly  
Pressure contact

**Double Thyristor Module  
For Phase Control  
MTx-200-28-C1**

Mean on-state current	$I_{TAV}$	200 A
Repetitive peak off-state voltage	$V_{DRM}$	2600 ÷ 2800 V
Repetitive peak reverse voltage	$V_{RRM}$	
Turn-off time	$t_q$	250 $\mu$ s
$V_{DRM}, V_{RRM}, V$	2600	2800
Voltage code	26	28
$T_j, ^\circ C$	- 40 ÷ 125	



All dimensions in millimeters (inches)

## MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions
<b>ON-STATE</b>				
$I_{TAV}$	Mean on-state current	A	200 237	$T_c=93\text{ }^\circ\text{C}$ ; $T_c=85\text{ }^\circ\text{C}$ ; 180° half-sine wave; 50 Hz
$I_{TRMS}$	RMS on-state current	A	314	$T_c=93\text{ }^\circ\text{C}$ ; 180° half-sine wave; 50 Hz
$I_{TSM}$	Surge on-state current	kA	5.5 6.3	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p=10\text{ ms}$ ; single pulse; $V_D=V_R=0\text{ V}$ ; Gate pulse: $I_G=2\text{ A}$ ; $t_{GP}=50\text{ }\mu\text{s}$ ; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
			6.0 6.9	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p=8.3\text{ ms}$ ; single pulse; $V_D=V_R=0\text{ V}$ ; Gate pulse: $I_G=2\text{ A}$ ; $t_{GP}=50\text{ }\mu\text{s}$ ; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
$I^2t$	Safety factor	$\text{A}^2\text{s}\cdot 10^3$	150 195	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p=10\text{ ms}$ ; single pulse; $V_D=V_R=0\text{ V}$ ; Gate pulse: $I_G=2\text{ A}$ ; $t_{GP}=50\text{ }\mu\text{s}$ ; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
			145 195	$T_j=T_{j\text{ max}}$ $T_j=25\text{ }^\circ\text{C}$ 180° half-sine wave; $t_p=8.3\text{ ms}$ ; single pulse; $V_D=V_R=0\text{ V}$ ; Gate pulse: $I_G=2\text{ A}$ ; $t_{GP}=50\text{ }\mu\text{s}$ ; $di_G/dt\geq 1\text{ A}/\mu\text{s}$
<b>BLOCKING</b>				
$V_{DRM}, V_{RRM}$	Repetitive peak off-state and Repetitive peak reverse voltages	V	2600÷2800	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$ ; 180° half-sine wave; 50 Hz; Gate open
$V_{DSM}, V_{RSM}$	Non-repetitive peak off-state and Non-repetitive peak reverse voltages	V	2700÷2900	$T_{j\text{ min}} < T_j < T_{j\text{ max}}$ ; 180° half-sine wave; single pulse; Gate open
$V_D, V_R$	Direct off-state and Direct reverse voltages	V	$0.75\cdot V_{DRM}$ $0.75\cdot V_{RRM}$	$T_j=T_{j\text{ max}}$ ; Gate open
<b>TRIGGERING</b>				
$I_{FGM}$	Peak forward gate current	A	6	$T_j=T_{j\text{ max}}$
$V_{RGM}$	Peak reverse gate voltage	V	5	
$P_G$	Gate power dissipation	W	3	$T_j=T_{j\text{ max}}$ for DC gate current
<b>SWITCHING</b>				
$(di_T/dt)_{\text{crit}}$	Critical rate of rise of on-state current non-repetitive (f=1 Hz)	$\text{A}/\mu\text{s}$	200	$T_j=T_{j\text{ max}}$ ; $V_D=0.67\cdot V_{DRM}$ ; $I_{TM}=2\text{ }I_{TAV}$ ; Gate pulse: $I_G=2\text{ A}$ ; $t_{GP}=50\text{ }\mu\text{s}$ ; $di_G/dt\geq 2\text{ A}/\mu\text{s}$
<b>THERMAL</b>				
$T_{\text{stg}}$	Storage temperature	$^\circ\text{C}$	- 40 ÷ 50	
$T_j$	Operating junction temperature	$^\circ\text{C}$	- 40 ÷ 125	
$T_{c\text{ op}}$	Operating temperature	$^\circ\text{C}$	- 40 ÷ 125	
<b>MECHANICAL</b>				
a	Acceleration under vibration	$\text{m}/\text{s}^2$	50	

## CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
<b>ON-STATE</b>					
$V_{TM}$	Peak on-state voltage, max	V	2.00	$T_j=25\text{ }^\circ\text{C}; I_{TM}=785\text{ A}$	
$V_{T(TO)}$	On-state threshold voltage, max	V	0.90	$T_j=T_{j\text{ max}};$	
$r_T$	On-state slope resistance, max	m $\Omega$	1.100	$0.5\pi I_{TAV} < I_T < 1.5\pi I_{TAV}$	
$I_L$	Latching current, max	mA	700	$T_j=25\text{ }^\circ\text{C}; V_D=12\text{ V};$ Gate pulse: $I_G=2\text{ A};$ $t_{GP}=50\text{ }\mu\text{s}; di_G/dt \geq 1\text{ A}/\mu\text{s}$	
$I_H$	Holding current, max	mA	300	$T_j=25\text{ }^\circ\text{C};$ $V_D=12\text{ V};$ Gate open	
<b>BLOCKING</b>					
$I_{DRM}, I_{RRM}$	Repetitive peak off-state and Repetitive peak reverse currents, max	mA	50	$T_j=T_{j\text{ max}};$ $V_D=V_{DRM}; V_R=V_{RRM}$	
$(dv_D/dt)_{crit}$	Critical rate of rise of off-state voltage, min	V/ $\mu\text{s}$	1000	$T_j=T_{j\text{ max}};$ $V_D=0.67\cdot V_{DRM};$ Gate open	
<b>TRIGGERING</b>					
$V_{GT}$	Gate trigger direct voltage, max	V	3.50	$T_j=T_{j\text{ min}}$	$V_D=12\text{ V}; I_D=3\text{ A};$ Direct gate current
			2.00	$T_j=25\text{ }^\circ\text{C}$	
			1.50	$T_j=T_{j\text{ max}}$	
$I_{GT}$	Gate trigger direct current, max	mA	250	$T_j=T_{j\text{ min}}$	
			150	$T_j=25\text{ }^\circ\text{C}$	
			100	$T_j=T_{j\text{ max}}$	
$V_{GD}$	Gate non-trigger direct voltage, min	V	0.25	$T_j=T_{j\text{ max}};$ $V_D=0.67\cdot V_{DRM};$	
$I_{GD}$	Gate non-trigger direct current, min	mA	10.00	Direct gate current	
<b>SWITCHING</b>					
$t_{gd}$	Delay time	$\mu\text{s}$	2.50	$T_j=25\text{ }^\circ\text{C}; V_D=0.4\cdot V_{DRM}; I_{TM}=I_{TAV};$ Gate pulse: $I_G=2\text{ A};$ $t_{GP}=50\text{ }\mu\text{s}; di_G/dt \geq 2\text{ A}/\mu\text{s}$	
$t_q$	Turn-off time, max	$\mu\text{s}$	250	$dv_D/dt=50\text{ V}/\mu\text{s}; T_j=T_{j\text{ max}}; I_{TM}=I_{TAV};$ $di_R/dt=-10\text{ A}/\mu\text{s}; V_R=100\text{ V};$ $V_D=0.67\text{ }V_{DRM}$	
<b>THERMAL</b>					
$R_{thjc}$	Thermal resistance, junction to case			180° half-sine wave, 50 Hz	
	per module	$^\circ\text{C}/\text{W}$	0.0550		
	per arm	$^\circ\text{C}/\text{W}$	0.1100		
$R_{thch}$	Thermal resistance, case to heatsink				
	per module	$^\circ\text{C}/\text{W}$	0.0200		
	per arm	$^\circ\text{C}/\text{W}$	0.0400		
<b>INSULATION</b>					
$V_{ISOL}$	Insulation test voltage	kV	3.00	Sine wave, 50 Hz;	t=1 min
			3.60	RMS	t=1 sec
<b>MECHANICAL</b>					
$M_1$	Mounting torque (M6) <sup>1)</sup>	Nm	6.00	Tolerance $\pm 15\%$	
$M_2$	Terminal connection torque (M8) <sup>1)</sup>	Nm	9.00	Tolerance $\pm 15\%$	
w	Weight	g	800		

PART NUMBERING GUIDE						NOTES				
MT	3	-	200	-	28	-	C1	-	N	
1	2		3		4		5		6	
1. Thyristor module (MT) Thyristor – Diode module (MT/D) Diode – Thyristor module (MD/T) 2. Circuit Schematic 3. Average On-state Current, A 4. Voltage Code 5. Package Type (M.C1) 6. Ambient Conditions: N – Normal										
										<sup>1)</sup> The screws must be lubricated

The information contained herein is confidential and protected by Copyright.  
 In the interest of product improvement, Proton-Electrotex reserves the right to change data sheet without notice.